



Applikator 4400 with LED kit

https://vimeo.com/504396584



SIGNIFICANT EFFICIENCY GAIN AND TIME SAVING IN YOUR ADHESIVE MEDIA APPLICATIONS

- Lamination of any kind of adhesive material and mounting up to 65 mm (2 ½") thickness
- Working width 170 cm (67")
- → Modular system: base model of 2,05 m 6′ 9″ expandable by sections of 2,38 m 7′ 10″. Chose your size upon order or have it expanded later.
- Electrical motors as the source for controlling the roller's elevation motion and safety control by laser sensor
- Adjustable pressure from both ends of the gantry with 3 pre-set levels for precise pressure application
- Roller stays parallel to the table surface, wherever the media is positionned on the working surface.
- Assembled on site within a few hours by one technician. The table will fit in any working environment, even with narrow access.
- Laminated glass for a smooth diffusion of backlighting. LED lighting system available as an option
- Antistatic, self-healing and phtalate free PVC mat, thickness of 4 mm, cut to the table size, included with the machine
- Adjustable height upon installation 80/90/100 cm 31 ½"/35 ½" /39"

MODULAR AND EVOLUTIONARY SYSTEM

EVOLUTIONARY APPLIKATOR - WIDTH: 1,70 M - 67"

This modular system is expandable by modules measuring 2,38 m - 7'10" without limitations, either upon ordering or also field expandable.

Select the format that suits your needs today without wondering about future needs.

This lamination table can bring a lot of benefits to your operation and will match the evolution of your company.

Length: base module 2,38 m - 7' 10'' expandable by the same size of 2,38 m - 7' 10''.

Delivered with standard feet.

Use of castors is not suitable with the Grandé range.



CUSTOMIZE YOUR LAMINATION TABLE

Give your creative and finishing touch to your AppliKator table by customizing it with your brand logo or decorative design as illustrated in the image below.

Closing panels not supplied with the machine. Cutting drawings are available on demand.



OPTIONS

SUPPLY OF ADHESIVE ROLLS


APPSUPAXE

Adhesive roll holder



APPFREIN

Adhesive roll holder on an aluminium self-blocking shaft. Delivered without shaft



AX 1650

Self-blocking shaft in 165 - 65"





STORING & CUTTING

STORING SYSTEM

To be installed at the end of the table.

Delivered without shaft




SHELF

Adaptable on the long or short edge of the table



CUTTING BAR ADAPTATION 165 CM

Perfect for works in series. The cutting bar is easily removable from its location.



LED LIGHTING SYSTEM

Directly connected to the power supply of the machine. Improves accuracy for the most demanding jobs.







→ TECHNICAL DATA

| | APP 2000 | APP 4400 | APP 6800 | APP 9200 | |
|--------------------------------|---|--------------------------------------|--|--|--|
| Usable length | 208 cm – 6' 10" | 445 cm – 14' 6" | 683 cm – 22' 5" | 921 cm – 30′ 3″ | |
| Total length | 238 cm – 7' 10" | 476 cm – 15' 8" | 714 cm – 23′ 5″ | 952 cm – 31' 3" | |
| Usable width | 170 cm – 67" | | | | |
| Total width | 227 cm – 90" | | | | |
| Height | Adjustable 80, 90, 100 cm (2 ft 7 $\frac{1}{2}$ " – 2 ft 11 $\frac{1}{2}$ " – 3 ft 3 $\frac{1}{3}$ ") upon installation | | | | |
| Mounting thickness | 6,5 cm – 2 ½" | | | | |
| Surface of the table | Glass panels | | | | |
| Antistatic PVC mat | Thickness 4 mm | | | | |
| Optional castors | Yes | Yes No | | | |
| Voltage | 110 & 230 V - 50 / 60 Hz | | | | |
| Power | 400 W | | | | |
| Weight without LED | 300 kg – 660 lb | 470 kg – 1040 lb | 720 kg – 1590 lb | 970 kg – 2140 lb | |
| | 2 Pallets | 2 Pallets | 3 Pallets | 3 Pallets | |
| Shipping dimension without LED | 232 x 72 x 100 cm 93" x 28" x 39" | 232 x 72 x 100 cm 93" x 28" x 39" | (x2) = 232 x 130 x 100 cm 93" x 28" x 39" | (x2) = 232 x 130 x 100 cm 93" x 28" x 39" | |
| WxDxH | 232 x 72 x 75 cm 93" x 28" x 30" | 232 x 72 x 130 cm 93" x 28" x 51" | (x1) = 232 x 130 x 75 cm 93" x 28" x 30" | (x1) = 232 x 130 x 130 cm 93" x 28" x 51" | |
| Shipping weight without LED | 400 kg – 882 lb | 570 kg – 1250 lb | 850 kg - 1875 lb | 1150 kg - 2530 lb | |





